

Stratix IV Military Temperature Range Support

Introduction

As part of the Altera® initiative to provide enhanced commercial off-the-shelf (COTS) devices for military applications, the temperature range for the Stratix® IV device family has been extended to enable operation across the military temperature range (-55°C to 125°C). This extension allows military programs to benefit from the new technology and economies of scale by using commercially available Stratix IV FPGAs. Stratix IV FPGAs are extremely robust and capable of operating across a wide temperature range with excellent reliability.

Military Temperature Support

Military temperature operation requires additional timing margin over industrial temperature operation to compensate for the potentially increased variation of delay across temperature.

Altera recommends that customers use military temperature grade devices for production. However, customers may substitute industrial temperature grade for military temperature grade devices during the prototyping phase because of the shorter lead times of the industrial temperature grade devices.

Use the following guidelines to compile your design using industrial or military devices:

- When using military models through industrial devices, select an applicable I3 part code and update the **Operating Settings and Conditions** dialog box to reflect -55° C (Minimum) and 125° C (Maximum) junction temperatures before compiling or recompiling your design.
- When using military models through military devices, select an applicable M3 part code and compile or recompile your design.

Table 1 lists the Stratix IV device part numbers that support the industrial and military temperatures.

Table 1. Stratix IV Industrial and Military Temperature Device Part Numbers

| Item | Device Part Number | | Package |
|------|------------------------|----------------------|---------|
| | Industrial Temperature | Military Temperature | |
| 1 | EP4SGX70DF29I3 | EP4SGX70DF29M3 | F780 |
| 2 | EP4SGX70HF35I3 | EP4SGX70HF35M3 | F1152 |
| 3 | EP4SGX110DF29I3 | EP4SGX110DF29M3 | F780 |
| 4 | EP4SGX110HF35I3 | EP4SGX110HF35M3 | F1152 |
| 5 | EP4SGX180DF29I3 | EP4SGX180DF29M3 | F780 |
| 6 | EP4SGX180HF35I3 | EP4SGX180HF35M3 | F1152 |
| 7 | EP4SGX180KF40I3 | EP4SGX180KF40M3 | F1517 |
| 8 | EP4SGX230DF29I3 | EP4SGX230DF29M3 | F780 |
| 9 | EP4SGX230HF35I3 | EP4SGX230HF35M3 | F1152 |
| 10 | EP4SGX230KF40I3 | EP4SGX230KF40M3 | F1517 |
| 11 | EP4SE230F29I3 | EP4SE230F29M3 | F780 |

Software Support

The Stratix IV military temperature grade device models are supported in the following versions of these tools:

- The PowerPlay Early Power Estimator or PowerPlay Power Analyzer software, version 11.0 or later.
Download from www.altera.com/support/devices/estimator/pow-powerplay.html.
- The Quartus II software, version 11.0 or later.
Download from www.altera.com/products/software/quartus-ii/subscription-edition/qts-se-index.html.

Characterization Report

Characterization reports are available upon request from your local Altera sales representative. For contact information, refer to www.altera.com/corporate/contact/con-index.html.



101 Innovation Drive
San Jose, CA 95134
www.altera.com

Copyright © 2011 Altera Corporation. All rights reserved. Altera, The Programmable Solutions Company, the stylized Altera logo, specific device designations, and all other words and logos that are identified as trademarks and/or service marks are, unless noted otherwise, the trademarks and service marks of Altera Corporation in the U.S. and other countries. All other product or service names are the property of their respective holders. Altera products are protected under numerous U.S. and foreign patents and pending applications, maskwork rights, and copyrights. Altera warrants performance of its semiconductor products to current specifications in accordance with Altera's standard warranty, but reserves the right to make changes to any products and services at any time without notice. Altera assumes no responsibility or liability arising out of the application or use of any information, product, or service described herein except as expressly agreed to in writing by Altera Corporation. Altera customers are advised to obtain the latest version of device specifications before relying on any published information and before placing orders for products or services.